



## File ceiling

code F1202.827X/01



### PRODUCT DESCRIPTION

Direct light indoor ceiling lamp made of extruded aluminum 6060, complete with led; color rendering index CRI >90. Professional led 25.6 W modules assembled and wired on extruded aluminum heatsink with high performance reflector, equipped with harmonic steel springs for installation in the profile Tools free; wiring through 5 cables with quick coupling terminal blocks; protocol On/Off. Lamp with color finish white; in polycarbonate with diffusing film. Degree of protection IP40/IP43.

### PRODUCT SPECS

|                              |                         |
|------------------------------|-------------------------|
| Installation method          | Ceiling surface mounted |
| Light source                 | LED                     |
| Absorbed power               | 25,6 W                  |
| Color temperature            | 2700K                   |
| Color rendering index CRI    | >90                     |
| Optic                        | Microprismatic diffuser |
| Finishing                    | White                   |
| Luminous flux of the product | 1928 lm                 |
| Luminous efficiency          | 75 lm/W                 |
| MacAdam color tolerance      | 3                       |
| Life time estimate           | 50000h Ta 25° L80B10    |
| Protocol                     | On/Off                  |
| Energy efficiency class      | E                       |
| Weight                       | 1.92 Kg                 |
| Dimension                    | L1140 mm                |
| IP Grade                     | IP40                    |
| Power supply                 | 220-240V 50-60Hz        |

### WEB PAGE



### ASSEMBLY INSTRUCTIONS

