

## File Suspension

code F1302.8HCP/01



### FILE opal LED



### PRODUCT DESCRIPTION

Direct light indoor suspension lamp made of extruded aluminum 6060, complete with led; color rendering index CRI >90. Professional led modules assembled and wired on extruded aluminum heatsink with high performance reflector, equipped with harmonic steel springs for installation in the profile Tools free; wiring through 5 cables with quick coupling terminal blocks; protocol On/Off. Lamp with color finish white; in polycarbonate with diffusing film. Degree of protection IP40/IP43.

### PRODUCT SPECS

|                           |                             |
|---------------------------|-----------------------------|
| Installation method       | Suspension                  |
| Light source              | LED                         |
| Absorbed power            | 25,6 W                      |
| Color temperature         | Horticulture                |
| Color rendering index CRI | >90                         |
| Optic                     | Opal polycarbonate diffuser |
| Finishing                 | White                       |
| MacAdam color tolerance   | 3                           |
| Life time estimate        | 50000h Ta 25° L80B10        |
| Protocol                  | On/Off                      |
| Energy efficiency class   | E                           |
| Weight                    | 2.00 Kg                     |
| Dimension                 | L1140 mm                    |
| IP Grade                  | IP40                        |
| Power supply              | 220-240V 50-60Hz            |

### WEB PAGE



### ASSEMBLY INSTRUCTIONS



