



## File Wall

code F1401.840PD/01



### PRODUCT DESCRIPTION

Direct light indoor wall lamp made of extruded aluminum 6060, complete with led; color rendering index CRI >90. Professional led 19.2 W modules assembled and wired on extruded aluminum heatsink with high performance reflector, equipped with harmonic steel springs for installation in the profile Tools free; wiring through 5 cables with quick coupling terminal blocks; protocol Dimmable Dali; polycarbonate with diffusing film. Protection rating IP40/IP43.

### PRODUCT SPECS

|                              |                             |
|------------------------------|-----------------------------|
| Installation method          | Wall surface mounted        |
| Light source                 | LED                         |
| Absorbed power               | 19,2 W                      |
| Color temperature            | 4000K                       |
| Color rendering index CRI    | >90                         |
| Optic                        | Opal polycarbonate diffuser |
| Finishing                    | White                       |
| Luminous flux of the product | 1114 lm                     |
| Luminous efficiency          | 58 lm/W                     |
| MacAdam color tolerance      | 3                           |
| Life time estimate           | 50000h Ta 25° L80B10        |
| Protocol                     | Dimmable Dali               |
| Energy efficiency class      | E                           |
| Weight                       | 1.56 Kg                     |
| Dimension                    | L860 mm                     |
| IP Grade                     | IP40                        |
| Power supply                 | 220-240V 50-60Hz            |

### WEB PAGE



### ASSEMBLY INSTRUCTIONS

