

## File 2 outdoor ceiling 24W/m

code F2226.840X/01



### PRODUCT DESCRIPTION

Ceiling luminaire IP54 outdoor, direct and diffused light. Body in extruded aluminum 6060, head in die-cast aluminum light proof, led SMD professional 24W/mt color temperature 4000K, assembled on rigid pcb with spray coating treatment for moisture protection, mounted and wired on ARS1 anodized aluminum extruded heatsink with additional transparent palsun protection to prevent contact to the LEDs during installation or maintenance, quick installation tools free by means of Click system with double-click harmonic steel springs for a first clamping to the profile that allows the wiring to the electrical network, to quick coupling without using screws. Integrated electronic power supply.

### PRODUCT SPECS

|                              |                         |
|------------------------------|-------------------------|
| Installation method          | Ceiling surface mounted |
| Light source                 | LED                     |
| Absorbed power               | 51,2 W                  |
| Color temperature            | 4000K                   |
| Color rendering index CRI    | >90                     |
| Optic                        | Microprismatic diffuser |
| Finishing                    | White                   |
| Luminous flux of the product | 4210 lm                 |
| Luminous efficiency          | 82 lm/W                 |
| MacAdam color tolerance      | 3                       |
| Life time estimate           | 50000h Ta 25° L80B10    |
| Protocol                     | On/Off                  |
| Energy efficiency class      | E                       |
| Dimension                    | L2265 mm                |
| Power supply                 | 220-240V 50-60Hz        |

### WEB PAGE



