




## Microfile recessed

code MF023.827/01



### MICROFILE LED



### PRODUCT DESCRIPTION

Direct light recessed with frame lamp, indoor, made of extruded aluminium 6060 square section measuring 19,8x19,5 mm; complete with led; CRI color rendering index >90. Professional led modules [power] assembled and wired; protocol [protocol]. Epoxy powder coated with [finish] color finish; complete with polycarbonate [diffuser] with diffusing film. Protection degree IP40.

### PRODUCT SPECS

|                              |                     |
|------------------------------|---------------------|
| Installation method          | Recessed with frame |
| Light source                 | Linea Led           |
| Absorbed power               | 33 W                |
| Color temperature            | 2700K               |
| Color rendering index CRI    | >90                 |
| Finishing                    | White               |
| Luminous flux of the product | 1600 lm             |
| Luminous efficiency          | 48 lm/W             |
| Protocol                     | On/Off              |
| Energy efficiency class      | D                   |
| Weight                       | 0.80 Kg             |
| Dimension                    | L1515 mm            |
| Hole size                    | 24xL+2 mm           |
| IP Grade                     | IP40                |
| Protection Class             | Class III appliance |
| Power supply/Transformer     | Not included        |
| Protocol                     | See power supply    |

### WEB PAGE



### ASSEMBLY INSTRUCTIONS



