

Nyx Frame TF50F Fixed for plasterboard

code NF023.930W/01





PRODUCT DESCRIPTION

Recessed ceiling luminaire with round frame, with fixed optics for accent and diffuse lighting. Light source in back anti-glare position. Available in versions for plasterboard installation. With integrated LED source with 99.9% pure aluminium metallic reflector. Body and body in painted aluminum. Remote power available as an accessory. IP20/IP54. Insulation class III.

PRODUCT SPECS

Installation method	Recessed with frame
Light source	LED
Absorbed power	12 W / 18 W
Color temperature	3000K
Color rendering index CRI	>90
Optic	Wide 46°
Finishing	White
Luminous flux of the product	1289 lm / 2257 lm
Luminous efficiency	107 lm/W / 125 lm/W
MacAdam color tolerance	2
Life time estimate	2SCDM 50.000h L90 B10 ta25°
Energy efficiency class	D
Weight	0.25 Kg
Dimension	H116 Ø75 mm
Hole size	70 mm
IP Grade	IP20/54
Protection Class	Class III appliance
Product Spec	Circular shape
Power supply/Transformer	Not included
Protocol	See power supply



WEB PAGE



ASSEMBLY INSTRUCTIONS



MANDATORY ACCESSORIES

AE350.16C (Copia)



code AE350.15C

Electronic power supply current

AE500.20C1




code AE500.20C1

Electronic power supply current

OPTIONAL ACCESSORIES

Accessori Lens ø 50 Elissoidal lens Ø 50



code L050E


uncategorized

Warning: Not suitable with halogen lamp

Technical Sheet



Accessori Lens ø 50 Asymmetric lens Ø 50



code L050A


uncategorized

Warning: Not suitable with halogen lamp

Technical Sheet



Accessori Lens ø 50 Honey comb Ø 50



code L050R

uncategorized

Technical Sheet

